

TIA-3000 Measurement Systems

PRODUCT SUMMARY

The TIA-3000 Measurement Systems are detector-based absolute standards for a variety of high-accuracy measurements. Off-the-shelf configurations include thermo-electrically cooled silicon and indium gallium arsenide (InGaAs) detectors. Options include high-accuracy photometric correction filters ($f1' \sim 0.8\%$), flat-response filters, trap detectors and ANVIS-compatibility filters with field-of-view lenses making the TIA-3000 the standard for any light measurement requirement.

The heart of the TIA-3000 is its transimpedance amplifier. The state-of-the-art design of the transimpedance amplifier allows for extremely low dark-current levels (3 femptoamps, 3×10^{-15} amps, at room temperature with the silicon detector) and excellent stability. This stability and sensitivity is 10 times more sensitive than anything else previously available, making it the ultimate tool for any standards lab.

The TIA-3000 incorporates 8 different ranges with a 0-to-10-volt output for each range.

Standard calibrations, directly traceable to NIST, are available for any configuration of the TIA-3000 from Gamma Scientific's world-renowned standards lab.



FEATURES

- *Temperature-stabilized silicon and InGaAs detectors available covering 200 – 1700 nm*
- *Temperature-stabilized correction filters available*
- *High-accuracy photopic correction $f1' \sim 0.8\%$*
- *ANVIS-compatibility filters and lenses*
- *High sensitivity down to 10^{-15} Watts or 10^{-8} Lux*
- *8 decades of dynamic range*
- *0-to-10-volt output for each decade*
- *RS-232 computer control*

APPLICATIONS

- *Display measurement photometry*
- *LED radiometry*
- *Night-vision compatibility measurements*
- *Metrology lab primary standard detector*
- *Customized optics available for any application*



GAMMA SCIENTIFIC

8581 Aero Drive San Diego, CA 92123 Ph (858) 279-8034 Fax (858) 576-9286

Website: www.gamma-sci.com

TIA-3000 Measurement Systems

SPECIFICATIONS

Gain	10 ¹⁰ to 10 ⁴ volts/amp
Range	Eight decades; automatic or manual dial control
Output	0 to 10 VDC for each gain setting
Linearity	<0.25% non-linearity for all ranges
Temperature Variation	<5 ppm (parts -per-million) per degree Celsius
Noise	<20 microvolts on the 10 ¹⁰ range
Frequency Roll -Off	<10 Hz on 10 ¹⁰ range for output >1 volt
Length (Amplifier)	4.15 inches (10.5 cm)
Diameter (Amplifier)	2.5 inches (6.4 cm)
Length (TE Cooler control box)	12 inches (30.5 cm)
Width (TE Cooler control box)	11.3 inches (28.7 cm)
Height (TE Cooler control box)	4.5 inches (11.4 cm)
Temperature Stability	Short term (1 hr.) <0.001 °C, long term (24 hr.) <0.003 °C
Bipolar Output Current	+ 1.5 amp max
Maximum TEC Output Power	12 watts
Power	100-240 VAC, 50-60 Hz

Note: Specifications obtained from independent third-party testing laboratory



GAMMA SCIENTIFIC

8581 Aero Drive San Diego, CA 92123 Ph (858) 279-8034 Fax (858) 576-9286

Website: www.gamma-sci.com